



U. S. Department of Homeland Security  
**United States Coast Guard**  
**Certificate of Approval**

Coast Guard Approval Number: 162.060/13/4

Expires: 02 October 2028

BALLAST WATER MANAGEMENT SYSTEM  
Filtration/Chemical Injection

JFE Engineering Corporation  
2-1 Suehiro-cho, Tsurumi-ku  
Yokohama 230-8611 JAPAN

Name of BWMS: JFE BallastAce

Capacities: 500-4,000 m3/h

This is to certify that the above listed BWMS, with the listed treatment capacities, has been satisfactorily examined and tested by Independent Lab Control Union Certifications in accordance with the requirements contained in 46 CFR 162.060. The system shall be installed and operated in accordance with each applicable Operation, Maintenance, and Safety Manual. JFE BallastAce Instruction Manual, Edition U-2, Rev. 0-25, dated January 27, 2020  
JFE BallastAce Instruction Manual, Edition U-3, Rev. 1-29, dated April 22, 2021  
JFE BallastAce Instruction Manual, Edition U-4, Rev. 2-0, dated May 17, 2021

Installation Limitations: See Appendix

Operational Limitations: See Appendix

The BWMS must be marked in accordance with 46 CFR 162.060-22. A copy of this Type Approval Certificate shall be carried on board a vessel fitted with the BWMS at all times.

Vessel owners/operators are expected to consult with the manufacturer to ensure the BWMS's operational limitations and treatment flow rates are acceptable for the water frequented by their vessels.

This certificate supersedes Approval number 162.060/13/3 dated May 6, 2021; update includes alternate control panel, software update and renewal.

\*\*\* End \*\*\*

THIS IS TO CERTIFY THAT the above named manufacturer has submitted to the undersigned satisfactory evidence that the item specified herein complies with the applicable laws and regulations as outlined on the reverse side of this Certificate, and approval is hereby given. This approval shall be in effect until the expiration date hereon unless sooner canceled or suspended by proper authority.

GIVEN UNDER MY HAND THIS 02<sup>nd</sup> DAY OF  
OCTOBER 2023, AT WASHINGTON D.C.



Acting Chief, Engineering Division  
BY DIRECTION OF THE COMMANDANT



**TERMS:** The approval of the item described on the face of the Certificate has been based upon the submittal of satisfactory evidence that the item complies with the applicable provisions of the navigation and shipping laws and the applicable regulations in Title 33 and/or Title 46 of the Code of Federal Regulations. The approval is subject to any conditions noted on this Certificate and in the applicable laws and regulations governing the use of the item on vessels subject to Coast Guard inspection or on other vessels and boats.

Consideration will be given to an extension of this approval provided application is made 3 months prior to the expiration date of this Certificate.

The approval holder is responsible for making sure that the required inspections or tests of materials or devices covered by this approval are carried out during production as prescribed in the applicable regulations.

The approval of the item covered by this certificate is valid only so long as the item is manufactured in conformance with the details of the approved drawings, specifications, or other data referred to. No modification in the approved design, construction, or materials is to be adopted until the modification has been presented for consideration by the Commandant and confirmation received that the proposed alteration is acceptable.

**NOTICE:** Where a manufacturer of safety-at-sea equipment is offering for sale to the maritime industry, directly or indirectly, equipment represented to be approved, which fails to conform with either the design details or material specifications, or both, as approved by the Coast Guard, immediate action may be taken to invoke the various penalties and sanctions provided by law including prosecution under 46 U.S.C. 3318, which provides:

"A person that knowingly manufactures, sells, offers for sale, or possesses with intent to sell, any equipment subject to this part (*Part B. of Subtitle II of Title 46 U.S.C.*) and the equipment is so defective as to be insufficient to accomplish the purpose for which it is intended, shall be fined not more than \$10,000, imprisoned for not more than 5 years or both."

INSTALLATION LIMITATIONS

In addition to meeting 46 CFR 162.060, which approves the operation of this BWMS in U.S. waters, this type approval certificate also allows for the installation and operation of this BWMS on the following vessels and/or shipboard locations:

BWMS Edition	U.S. Flag Installation	Hazardous Location Installation (U.S. Flag) <sup>1</sup>	Hazardous Location Installation (Foreign Flag) <sup>2</sup>
BallastAce, U-2			X <sup>3</sup>
BallastAce, U-3			X <sup>4</sup>
BallastAce, U-4			X <sup>5</sup>

1) Models have been verified to meet the requirements of 46 CFR 111.105  
2) Subject to approval of the foreign administration  
3) The UV-T unit, control panel, chemical pump, disinfectant tanks, disinfectant dissolution unit, neutralizer dissolution unit and butterfly valves must remain outside of hazardous locations.  
4) The control panel, chemical pump, disinfectant tanks, disinfectant dissolution unit, neutralizer dissolution unit and butterfly valves must remain outside of hazardous locations.  
5) The control panel, chemical pump, disinfectant tanks, neutralizer dissolution unit and butterfly valves must remain outside of hazardous locations.

Note: "X" indicates approval for installation.

OPERATIONAL LIMITATIONS

U-2 (Part A) & U-3 (Part A) Edition

Salinity: Not Applicable  
Water Temperature: Not Applicable  
Hold Time: >24 Hours  
                  >36 Hours if using the Kanagawa Filter in Marine Water (>28PSU)  
Maximum Disinfectant Dose: 20 mg/L as total available chlorine  
Filter Inlet Pressure: > 0.15 MPa

U-2 (Part B), U-3 (Part B) & U-4 Edition

Salinity: Not Applicable  
Water Temperature: Not Applicable  
Hold Time: >24 Hours  
                  >36 Hours if using the Kanagawa Filter in Marine Water (>28PSU)  
Maximum Disinfectant Dose: 15 mg/L as total available chlorine  
Total Residual Oxidant (TRO) range: 2.5- 14 mg/L as total available chlorine  
Maximum TRO Target Value: 12 mg/L as total available chlorine  
Filter Inlet Pressure: > 0.15 MPa

\*\*\* END \*\*\*