

Overall Length: 79 feet or more.

TUGSAFE INTERNATIONAL ADDENDUM

Guidelines for Inspected Towing Vessels Under 300 GRT

Date:

This job aid provides guidance for applicability of international conventions on towing vessels required to comply with 46 CFR Subchapter M that operate internationally. Requirements are based on length, build date and a tonnage measurement system. NVIC 11-93 Change 3 provides Coast Guard guidance on applicability of tonnage measurement systems.

Convention Length: Less than 79 feet.

Vessel Name: _____ Official Number:

Assigned GT-ITC tonnage: 300 to 399.

Certificates Requirement Applicability Cite Int'l Tonnage Certificate (ITC) ≥ 79 ft. ITC Article 7 and 46 CFR Part 69 1 Int'l Load Line Certificate (ILLC) 46 CFR Part 42 and ILLC Article 16 Cargo Ship Safety Radio Certificate (CSSRC) SOLAS I/12 300 GT-ITC 2,4 Marpol Annex IV Statement of Voluntary Compliance NVIC 01-09 (Guidance) 3,4 Int'l Ballast Water Management Statement of Voluntary Compliance CVC Policy 17-05 (Guidance) **Equipment and Document Spot-Checks** Requirement Applicability Cite Vessel equipped and in complance with applicable certificates. All N/A Global Maritime Distress and Safety System (GMDSS) 300 GT-ITC SOLAS IV and 47 CFR 80.161 300 GT-ITC Long Range Identification and Tracking (LRIT) SOLAS V/19-1 and 33 CFR 169.205

1. Applicability for new vessels (built on or after July 21, 1968) is \geq 79 ft. Applicability for existing vessels (built before July 21, 1968) is \geq 150 GRT.

2. Applies to all vessels that carry >15 persons (passengers and crew). Applies to all other vessel that are >400 GT-ITC ITC.

3. Applies to vessels designed or constructed to carry ballast water.

4. Although not mandatory and administered through a voluntary program, vessel owners who operate on international routes are encouraged to participate.

Developed by the United States Coast Guard Towing Vessel National Center of Expertise.