



# TUGSAFE INTERNATIONAL ADDENDUM

Guidelines for Inspected Towing Vessels Under 300 GRT

Date: \_\_\_\_\_

This job aid provides guidance for applicability of international conventions on towing vessels required to comply with 46 CFR Subchapter M that operate internationally. Requirements are based on length, build date and a tonnage measurement system. [NVIC 11-93 Change 3](#) provides Coast Guard guidance on applicability of tonnage measurement systems.

Vessel Name: \_\_\_\_\_ Official Number: \_\_\_\_\_

Overall Length: 79 feet or more. Convention Length: 79 feet or more. Assigned GT-ITC tonnage: 400 to 499.

**Note:** This vessel is allowed to use GRT for applicability of certain international certificates. If the owner elects to use GT-ITC for applicability of all certificates, regenerate this job aid using the "Assigned GT-ITC tonnage" option.

Certificates		
Requirement	Applicability	Cite
<input type="checkbox"/> Int'l Tonnage Certificate (ITC)	≥ 79 ft.	ITC Article 7 and 46 CFR Part 69
<input type="checkbox"/> Int'l Load Line Certificate (ILLC)	<sup>1</sup>	46 CFR Part 42 and ILLC Article 16
<input type="checkbox"/> Marpol Annex IV Statement of Voluntary Compliance	<sup>2,5</sup>	NVIC 01-09 ( <b>Guidance</b> )
<input type="checkbox"/> Int'l Air Pollution Prevention Certificate (IAPP)	400 GT-ITC	MARPOL Annex VI/6
<input type="checkbox"/> Int'l Energy Efficiency Certificate (IEE)	400 GT-ITC	IMO Resolution MEPC.203(62)
<input type="checkbox"/> Int'l Anti-Fouling System Certificate.	400 GT-ITC <sup>3</sup>	33 USC 3821 and AFS.1/Circ. 49
<input type="checkbox"/> Int'l Ballast Water Management Statement of Voluntary Compliance	<sup>4,5</sup>	CVC Policy 17-05 ( <b>Guidance</b> )
Equipment and Document Spot-Checks		
Requirement	Applicability	Cite
<input type="checkbox"/> Vessel equipped and in compliance with applicable certificates.	All	N/A
<input type="checkbox"/> Long Range Identification and Tracking (LRIT)	300 GT-ITC	SOLAS V/19-1 and 33 CFR 169.205
<input type="checkbox"/> Ship Energy Efficiency Management Plan (SEEMP)	400 GT-ITC	MARPOL VI/22

1. Applicability for new vessels (built on or after July 21, 1968) is ≥ 79 ft. Applicability for existing vessels (built before July 21, 1968) is ≥ 150 GRT.
2. Applies to all vessels that carry >15 persons (passengers and crew). Applies to all other vessel that are > 400 GT-ITC ITC.
3. Only required on vessels that have an anti-fouling system.
4. Applies to vessels designed or constructed to carry ballast water.
5. Although not mandatory and administered through a voluntary program, vessel owners who operate on international routes are encouraged to participate.

Developed by the United States Coast Guard [Towing Vessel National Center of Expertise](#).