

## **TUGSAFE INTERNATIONAL ADDENDUM**

Guidelines for Inspected Towing Vessels Under 300 GRT

Date:

This job aid provides guidance for applicability of international conventions on towing vessels required to comply with 46 CFR Subchapter M that operate internationally. Requirements are based on length, build date and a tonnage measurement system. NVIC 11-93 Change 3 provides Coast Guard guidance on applicability of tonnage measurement systems.

Vessel Name:

Official Number:

Overall Length: 79 feet or more. Convention Length: 79 feet or more. Assigned GT-ITC tonnage: Less than 300.

**Note:** This vessel is allowed to use GRT for applicability of certain international certificates. If the owner elects to use GT-ITC for applicability of all certificates, regenerate this job aid using the "Assigned GT-ITC tonnage" option.

Certificates		
Requirement	Applicability	Cite
Int'l Tonnage Certificate (ITC)	≥79 ft.	ITC Article 7 and 46 CFR Part 69
Int'l Load Line Certificate (ILLC)	1	46 CFR Part 42 and ILLC Article 16
Marpol Annex IV Statement of Voluntary Compliance	2,4	NVIC 01-09 (Guidance)
Int'l Ballast Water Management Statement of Voluntary Compliance	3,4	CVC Policy 17-05 (Guidance)
Equipment and Document Spot-Checks		
Requirement	Applicability	Cite
Vessel equipped and in complance with applicable certificates.	All	N/A

1. Applicability for new vessels (built on or after July 21, 1968) is  $\geq$  79 ft. Applicability for existing vessels (built before July 21, 1968) is  $\geq$  150 GRT.

2. Applies to all vessels that carry >15 persons (passengers and crew). Applies to all other vessel that are >400 GT-ITC ITC.

3. Applies to vessels designed or constructed to carry ballast water.

4. Not mandatory; however, vessel owners who operate on international routes are encouraged to participate.

Developed by the United States Coast Guard Towing Vessel National Center of Expertise.