

## **TUGSAFE INTERNATIONAL ADDENDUM**

Guidelines for Inspected Towing Vessels Under 300 GRT

Date:			

This job aid provides guidance for applicability of international conventions on towing vessels required to comply with 46 CFR Subchapter M that operate internationally. Requirements are based on length, build date and a tonnage measurement system. NVIC 11-93 Change 3 provides Coast Guard guidance on applicability of tonnage measurement systems.

Vessel Name:\_\_\_\_\_ Official Number:\_\_\_\_\_

Overall Length: 79 feet or more. Convention Length: 79 feet or more. Assigned GT-ITC tonnage: 300 to 399.						
Certificates						
Requirement	Applicability	Cite				
Int'l Tonnage Certificate (ITC)	≥ 79 ft.	ITC Article 7 and 46 CFR Part 69				
Int'l Load Line Certificate (ILLC)	1	46 CFR Part 42 and ILLC Article 16				
Cargo Ship Safety Radio Certificate (CSSRC)	300 GT-ITC	SOLAS I/12				
Marpol Annex IV Statement of Voluntary Compliance	2,4	NVIC 01-09 (Guidance)				
Int'l Ballast Water Management Statement of Voluntary Compliance	3,4	CVC Policy 17-05 (Guidance)				
Equipment and Document Spot-Checks						
Requirement	Applicability	Cite				
Vessel equipped and in complance with applicable certificates.	All	N/A				
Global Maritime Distress and Safety System (GMDSS)	300 GT-ITC	SOLAS IV and 47 CFR 80.161				
Long Range Identification and Tracking (LRIT)	300 GT-ITC	SOLAS V/19-1 and 33 CFR 169.205				

- Applicability for new vessels (built on or after July 21, 1968) is ≥ 79 ft. Applicability for existing vessels (built before July 21, 1968) is ≥ 150 GRT.
- 2. Applies to all vessels that carry >15 persons (passengers and crew). Applies to all other vessel that are > 400 GT-ITC ITC.
- 3. Applies to vessels designed or constructed to carry ballast water.
- 4. Although not mandatory and administered through a voluntary program, vessel owners who operate on international routes are encouraged to participate.

Developed by the United States Coast Guard Towing Vessel National Center of Expertise.